


PIGNONI

1/2" x 3/16"
per catene a rulli secondo
DIN 8187 - ISO/R 606



R. Garotti & F. gliò s.r.l.

SEMPLICI

Z	d _e	d _p	d _m	D ₁	A
8	38.5	33.18	21	8	14
9	41.5	37.13	25	8	14
10	46.2	41.10	28	8	14
11	49.6	45.07	31	8	16
12	53.9	49.07	35	8	16
13	58.4	53.06	39	8	16
14	62.8	57.07	43	8	16
15	66.8	61.09	47	8	16
16	70.9	65.10	50	10	18
17	74.9	69.11	50	10	18
18	78.9	73.14	50	10	18
19	82.9	77.16	50	10	18
20	88.9	81.19	50	10	18
21	91.0	85.22	60	12	20
22	95.0	89.24	60	12	20
23	99.0	93.27	60	12	20
24	103.0	97.29	60	12	20
25	107.1	101.33	60	12	20
26	111.2	105.36	70	16	20
27	115.4	109.40	70	16	20
28	119.4	113.42	70	16	20
29	123.4	117.46	70	16	20
30	127.5	121.50	70	16	20
31	131.5	125.54	70	16	20
32	135.5	129.56	70	16	20
33	139.6	133.60	70	16	20
34	143.6	137.64	70	16	20
35	147.6	141.68	70	16	20
36	151.7	145.72	70	16	25
37	155.7	149.76	70	16	25
38	159.8	153.80	70	16	25
39	163.8	157.83	70	16	25
40	167.8	161.87	70	16	25

PIGNONE

RAGGIO DENTE r ₃	13	mm
LARGHEZZA RAGGIO C	1.3	mm
LARGHEZZA DENTE PIGNONE B ₁	4.5	mm

CATENA

PASSO	12.7	mm
LARGHEZZA INTERNA	4.88	mm
RULLO Ø	7.75	mm

MATERIALE: C 45 UNI 7845