



PIGNONI SEMPLICI
DENTI TEMPRATI AD INDUZIONE
FORO + CAVA + FORI VITE



Cave DIN 6885 - UNI 6604



cava in linea con dente

D₁ Foro	B Larghezza cava	T₂ Profondità cava	M Viti
Ø 12 H7 ^{+0.018} / ₋₀	4 H9 ^{+0.030} / ₋₀	1,8 ^{+0.10} / ₋₀	M4
Ø 14 H7 ^{+0.018} / ₋₀	5 H9 ^{+0.030} / ₋₀	2,3 ^{+0.10} / ₋₀	M4
Ø 15 H7 ^{+0.018} / ₋₀	5 H9 ^{+0.030} / ₋₀	2,3 ^{+0.10} / ₋₀	M4
Ø 16 H7 ^{+0.018} / ₋₀	5 H9 ^{+0.030} / ₋₀	2,3 ^{+0.10} / ₋₀	M4
Ø 18 H7 ^{+0.018} / ₋₀	6 H9 ^{+0.030} / ₋₀	2,8 ^{+0.10} / ₋₀	M5
Ø 19 H7 ^{+0.021} / ₋₀	6 H9 ^{+0.030} / ₋₀	2,8 ^{+0.10} / ₋₀	M5
Ø 20 H7 ^{+0.021} / ₋₀	6 H9 ^{+0.030} / ₋₀	2,8 ^{+0.10} / ₋₀	M5
Ø 22 H7 ^{+0.021} / ₋₀	6 H9 ^{+0.030} / ₋₀	2,8 ^{+0.10} / ₋₀	M5
Ø 24 H7 ^{+0.021} / ₋₀	8 H9 ^{+0.036} / ₋₀	3,3 ^{+0.20} / ₋₀	M6
Ø 25 H7 ^{+0.021} / ₋₀	8 H9 ^{+0.036} / ₋₀	3,3 ^{+0.20} / ₋₀	M6
Ø 28 H7 ^{+0.021} / ₋₀	8 H9 ^{+0.036} / ₋₀	3,3 ^{+0.20} / ₋₀	M6
Ø 30 H7 ^{+0.021} / ₋₀	8 H9 ^{+0.036} / ₋₀	3,3 ^{+0.20} / ₋₀	M6
Ø 32 H7 ^{+0.025} / ₋₀	10 H9 ^{+0.036} / ₋₀	3,3 ^{+0.20} / ₋₀	M8
Ø 35 H7 ^{+0.025} / ₋₀	10 H9 ^{+0.036} / ₋₀	3,3 ^{+0.20} / ₋₀	M8
Ø 38 H7 ^{+0.025} / ₋₀	10 H9 ^{+0.036} / ₋₀	3,3 ^{+0.20} / ₋₀	M8
Ø 40 H7 ^{+0.025} / ₋₀	12 H9 ^{+0.043} / ₋₀	3,3 ^{+0.20} / ₋₀	M10
Ø 42 H7 ^{+0.025} / ₋₀	12 H9 ^{+0.043} / ₋₀	3,3 ^{+0.20} / ₋₀	M10
Ø 45 H7 ^{+0.025} / ₋₀	14 H9 ^{+0.043} / ₋₀	3,8 ^{+0.20} / ₋₀	M12
Ø 48 H7 ^{+0.025} / ₋₀	14 H9 ^{+0.043} / ₋₀	3,8 ^{+0.20} / ₋₀	M12
Ø 50 H7 ^{+0.025} / ₋₀	14 H9 ^{+0.043} / ₋₀	3,8 ^{+0.20} / ₋₀	M12